

Imperial Onyx Perla 24x48

Code: **IMP-ONX-PER-2448**

Collection: **Porcelain and Ceramic**

Product Details:

| | |
|------------------------|---------------|
| Material | Porcelain |
| Color | - |
| Surface | Lappato |
| Mounting Type: | Loose |
| Priced by: | sf |
| Sold by: | box |
| Sheet Size: | 24x48 |
| Chip Size (inch) | 23.7x47.25" |
| Chip Size (mm) | 600x1200 |
| Thickness | 3/8 |
| Sheet Coverage (sq.ft) | 7.750 |
| Variation: | V3 (moderate) |
| Porcelain Faces: | 17 |
| Porcelain Edges: | Rectified |

Packaging Info:

| | |
|--------------------------|-----------|
| Packing: | 2 pcs/box |
| Sq. Ft. Per Box: | 15.501 |
| Weight/box: | 69.850 |
| Sheet or Sq. Ft. weight: | 7.750 |

Areas of use

| | |
|------------------------|-----|
| Indoor Walls: | Yes |
| Light traffic floors: | Yes |
| High traffic floors: | Yes |
| Shower Walls: | Yes |
| Shower Floor: | No |
| Steam Room: | Yes |
| Swimming Pool: | No |
| Heat areas up to 150F: | Yes |
| Commercial Walls: | Yes |
| Commercial Floors: | Yes |



MIR[®]
Collections

2200 B Zanker Rd,
San Jose, CA 95131
Phone: +1 408 432 1000
Fax: +1 408 228 3924
www.mir-mosaic.com
E-mail: info@mir-mosaic.com

Additional Specs:

| | |
|----------------------|--------------------------|
| Breaking Strength: | â‰¥ 2000 N |
| Frost Resistance: | Resists |
| Stain Resistance: | Class 5 |
| Chemical Resistance: | Resists |
| Modulus of rupture: | â‰¥ 45 N/mm ² |

Maintenance and Installation:

| | |
|-----------------------|------------------------|
| Recommended Mortar: | Laticrete 254 Platinum |
| Recommended Grout: | Laticrete Permacolor |
| Grout joint interior: | 2mm |